

2022 Mudd-Ox 6 Wheel Amphibious Trailer XL

Chassis & Body

| | |
|-------------|--|
| Frame | Powder coated steel for long life and durability |
| Axles | 1.500" Diameter Axles |
| Tires | 26" x 14" x 12" Mudd-Ox Vendetta on 12" Mudd-Ox Beadlock Rim. |
| Floor Board | Wooden with handles for quick removal |
| Body | Vacuum formed lower body and optional skid plate, made from High Molecular Weight Polyethylene (HMWPE) |

Performance

| | |
|-------------------------------|---|
| Towing Speed - Land | Maximum 30 mph [A] |
| Towing Speed - Water | Maximum 10 mph [B] |
| Load Capacity | 2,000 lbs. (907 kg)(distributed evenly) Less the weight of any accessories [C][F] |
| Approach and Departure Angles | 25° Maximum |

Safety

| | |
|------------------|--|
| Safety | Optional Roll Over Protection System with a roll bar on each end of the trailer. |
| Usage Conditions | All weather, all terrain, -40°F to +110°F (-40°C to +43°C) |

Mudd-Ox, Inc.
 8525 W 750 N
 Shipshewana, IN 46565
 Phone: 260-768-7221
 Fax: 260-768-3074
www.muddox.net
info@muddox.net

Mudd-Ox

Custom Colors Available Upon Request



Ground Clearance & Ground Pressure

| | |
|------------------|--|
| Ground Clearance | 14" at center of vehicle 8" outer edge of vehicle |
| Ground Pressure | On Tires: 1 psi [D] Tracks: 0.25 psi [D] |

Weight & Dimensions

| | |
|------------------|---|
| Weight | 750 lbs |
| Outer Dimensions | 168" long w/ hitch, 123" long w/o hitch x 66" wide x 35" high on 26x14x12" Vendetta Tires |
| Inner Dimensions | 100" long at bottom, 119" long at top x 33" wide at bottom, 56" wide at top x 16" high. Fenders 12" wide (included in 56" wide at top measurement). |

Warranty

| | |
|----------|------------|
| Warranty | 1 year [E] |
|----------|------------|

Specifications are subject to change without notice.

- [A] Top speed depends on terrain conditions and drive train options.
 [B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)
 [C] See Owner's manual for accessory listing and weight.
 [D] Depending on weight of cargo and accessories onboard
 [E] See Vehicle Owner's Manuals for full warranty information.
 [F] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

| | |
|--------------------------------|--------------------------|
| Bearing Grease Zerk Relocation | Tire - Dual Wheel Kit |
| Rescue | Tracks - 20" Wide Ripsaw |
| Skid Plate | Transport Tie Downs |
| Safari Rack (Full/Half Length) | Twin Roll Bars |

Version 9/17/2021

