

## 2022 Mudd-Ox 8x8 Vengeance

### Engine

Type	Diesel	Gasoline EFI	Gasoline EFI
Model	VEN25	VEN31	VEN40
Brand	Kubota	Kohler	Briggs & Stratton
Power Output	24.8 HP / 18.5 kW	31 HP / 23.1 kW	40 HP / 30 kW
Torque	41.4 lbs. / 56.1 Nm	47.1 lbs. / 63.9 Nm	58.5 lbs. / 79.3 Nm
Displacement	54.8 CI / 898 CC	50.3 CI / 824 CC	60.6 CI / 993 CC
Cooling	Liquid-Cooled	Liquid-Cooled	Air-Cooled
Electrical	40 Amp	25 Amp, 60 Opt	50 Amp, 105 Opt
Battery	34 Series		

### Transmission

Transmission	Skid Steer T20 Dual Planetary with Split Shift for counter-rotation capability.
Brakes	Transmission/Mechanical
Clutch	CVT Continuously Variable Clutch maximizes engine power to transmission

### Controls & Instrumentation

Steering	Left & Right Steering Sticks
Parking Brake	Ratchet Style Mechanical
Instrumentation	Analog Dash Panel Left Mount
Gauges	Fuel Gauge Volt Meter Water Temperature [G] Transmission Fluid Temperature Hour Meter
Warning Lights	Engine Diagnostics (VEN31, VEN40) Low Oil Pressure Parking/Emergency Brake Tachometer (VEN40)
Throttle Cable	Heated Throttle Cable w/ Aluminum Base

### Chassis, Body & Lights

Frame	Powder coated steel for long life
Drive System	Standard Chain: Transmission single 60, rear four axles single 60. Front four axles HD Upgrade: Transmission twin 50, all axles twin 60.
Axles	1.500" Diameter Axles
Body	Vacuum formed upper body, lower hull and skid plate made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" Mudd-Ox Vendetta on 12" Mudd-Ox Bead Lock Rim
Lights	LED Headlights LED Tail Lights

### Performance

Speed - Land	17-25 mph (27-40 km/h) [A]
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	1,800 lbs. (816 Kg) (Distributed evenly) Less the weight of any accessories [C]
Load Capacity - Water	1,000 lbs. (454 Kg) (Distributed evenly) Less the weight of any accessories [C]
Turning Circle	Zero turning Radius
Towing Capacity	2,000 lbs. (907 Kg) [H]
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]
Rear Bench Seat	Optional

**Mudd-Ox, Inc.**  
8525 W 750 N  
Shipshewana, IN 46565  
Phone: 260-768-7221  
Fax: 260-768-3074  
www.muddox.net  
info@muddox.net

# Mudd-Ox

Custom Colors Available Upon Request



### Safety

Safety	Standard Fold Down Roll Over Protection System - Rear Roll Over Protection System available as an option. Front Seat Belts.
Fuel Capacity	12 US Gallons giving approx. 8-10 hours of operation 10.5 US Gallons with optional Rear Roll Bar
Operating Conditions	All Weather, all terrain, -40° F to +110° F (-40° C to +43° C)

### Ground Clearance & Ground Pressure

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 2 psi [D] Tracks 0.5 psi [D]

### Operation & Convenience

Self-Extraction Winch	5,000 lb. Winch Standard
Storage	Lockable Glove Box Cup Holders 12" x 28" Insert area over engine cover for holding light cargo
Electrical Output	Single 12 Volt Outlet Dual Port USB Outlet
Bilge Pump	Standard

### Weight & Dimensions

Shipping Weight	2,000 lbs.
Dimensions	123" long by 68" wide by 79" high with roll bar up. 61" high with roll bar down (on 26 x 14 x 12" Vendetta Tires)
Approach and Departure Angles	25 degrees maximum

### Warranty

Warranty	1 year or 500 hours limited warranty on Mudd-Ox Engine: See manufacturer's manual [E]
----------	---

Specifications are subject to change without notice.

- [A] Top speed depends on terrain conditions and drive train options.  
[B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)  
[C] See Owner's manual for accessory listing and weight.  
[D] Capacity includes occupants, cargo, and installed accessories.  
[E] See Owner's Manual for full warranty information.  
[F] Provides better flotation and allows for more carrying capacity in the [G] Only When equipped with 31 HP Kawasaki engine  
[H] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

### Accessories

A/C Unit (VEN40 only)	Rear Accessory Carrier - Main Mount
A/C Unit Brush Guard	Rear Seat - Standard
Alternator Upgrade	Rear Seat - Bench
Automatic Chain & Bearing Lubricator	Rescue
Auxiliary Switch Panel	Safari Rack (Full/Half Lengths)
Bearing Extension Kit	Snow Plow - 85"
Bearing Grease Zerk Relocation	Snow Plow - Boss V Blade
Brush Cage (Full/Half Length)	Spare Carrier - 5 Gallon Fuel Can w/ Can
Brush Guard	Spare Carrier - Tire
Cab - Aluminum	Tire - 26 x18 x12" Vendetta
Cab - Canvas (Full/Half Combo)	Tire - Dual Wheel Kit
Cab - Stereo Kit	Tool Box
Cargo Liner	Tracks - 16" Wide Adair
Cargo Platform	Tracks - 20" Wide Ripsaw
Chain HD Upgrade	Tracks - 21" Wide Beaver Dam
Dump Bed	Transport Tie Downs
Engine Remote Oil Drain	Twin Roll Bar Package
Fender Kit	Winch - 5000 lbs. Rear Mount
Float - Catwalk	Winch - Synthetic Rope Upgrade
Float - Front	Windshield
Heater w/ Defrost (VEN25, VEN31)	Windshield Cover - Cab
Light Bar 12-48"	Windshield Washer
Outboard Motor	Windshield Wiper

Version 9/17/2021