

2022 Mudd-Ox 8x8 XL

Engine

Type	Gasoline EFI
Model	XL57
Brand	Kubota
Power Output	57 HP / 42 kW
Torque	86.7 lbs. / 117.5 Nm
Displacement	1537 cc
Cooling	Liquid-Cooled
Electrical	105 Amp
Battery	65 Series

Transmission

Transmission	Mudd-Ox Hydrostatic
Brakes	Hydrostatic and Hydraulic Braking

Controls & Instrumentation

Steering	Ergonomic Left and Right Steering Controls
Parking Brake	Ratchet Style Mechanical
Instrumentation	Full Instrumentation Dash Panel
Gauges	Full Engine Power View & Diagnostics Fuel Gauge Volt Meter Hour Meter Coolant Temperature Hydraulic Temperature
Warning Lights	Check Engine Low Oil Pressure Neutral Light Parking/Emergency Brake

Chassis, Body & Lights

Frame	Powder coated steel for long life and durability
Drive System	#60-2 (Twin 60) Roller Chain
Axles	1,500" Solid Steel
Body	Vacuum formed upper body, lower body and skid plate, made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" x 12" Mudd-Ox Vendetta on 12" Mudd-Ox Bead Lock Rim
Lighting	LED Headlights & LED Tail Lights LED Brake & Reverse Lights w/ Optional Steering Wheel

Performance

Speed - Land	17-25 mph (27-40 km/h) [A]
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	2,000 lbs. (907 kg)(distributed evenly) Less the weight of any accessories [C]
Load Capacity - Water	1,000 lbs. (454 kg)(distributed evenly) Less the weight of any accessories [C]
Turning Circle	Zero turning radius, machine counter-rotates
Towing Capacity	2,500 lbs. (1,134 kg) [G]
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]
Rear Bench Seat	Optional

Mudd-Ox, Inc.
8525 W 750 N
Shipshewana, IN 46565
Phone: 260-768-7221
Fax: 260-768-3074
www.muddox.net
info@muddox.net

Mudd-Ox
Custom Colors Available Upon Request



Safety

Safety	Fold down Roll Over Protection System with seat belts for front two passengers. Rear Roll Over Protection System is available as an option. Mudd-Ox Hydrostatic precision control drive system enables safe control at all times while maneuvering in the most difficult terrains.
Fuel Capacity	12 US Gallons giving approx. 8-10 hours of operation 10.5 US Gallons with optional Rear Roll Bar
Operating Conditions	All weather, all terrain, -40°F to +110°F (-40°C to +43°C)

Ground Clearance

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 2 psi [D] Tracks: 0.5 psi [D]

Operation & Convenience

Self-Extraction Winch	5,000 lb. Capacity
Storage	Lockable glove box, Built in Cup Holders 12.5" x 28" Insert area over Engine Cover
Electrical Output	12V Outlet, Dual Port USB Outlet
Bilge Pump	Standard

Weight & Dimensions

Shipping Weight	2,290 lbs.
Dimensions	123" Long 68" Wide 79" High with Roll Bar Up, 61" High with Roll Bar Down (on 26 x 14 x 12" Vendetta Tires)
Approach and Departure angles	25° Maximum

Warranty

Warranty	1 year or 500 hours limited warranty on Mudd-Ox Engine: See manufacturer's manual [E]
----------	---

Specifications are subject to change without notice.

- [A] Top speed depends on terrain conditions and drive train options.
- [B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)
- [C] See Owner's manual for accessory listing and weight.
- [D] Depending on weight of person, cargo and accessories onboard
- [E] See Owner's Manual for full warranty information.
- [F] Provides better flotation and allows for more carrying capacity in the water.
- [G] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

A/C Unit	Rear Seat - Standard
A/C Unit Brush Guard	Rear Seat - Bench
Automatic Chain & Bearing Lubrication	Rescue
Auxiliary Switch Panel	Safari Rack (Full/Half Lengths)
Auxiliary Hydraulics	Snow Plow - 85"
Bearing Grease Zerk Relocation	Snow Plow - Boss V Blade
Brush Cage (Full/Half Length)	Spare Carrier - 5 Gallon Fuel Can
Brush Guard	Spare Carrier - Tire
Cab - Aluminum	Tire - 26x18 x12" Vendetta
Cab - Canvas (Full/Half Combo)	Tire - Dual Wheel Kit
Cab - Stereo Kit	Tool Box
Controls - Steering Wheel	Tracks - 16" Wide Adair
Cargo Liner	Tracks - 20" Wide Ripsaw
Cargo Platform	Tracks - 21" Wide Beaver Dam
Dump Bed	Transport Tie Downs
Engine Remote Oil Drain	Twin Roll Bar Package
Fender Kit	Winch - Synthetic Rope
Float - Catwalk	Winch - 5000 lbs. Rear Mount
Float - Front	Windshield
Heater w/ Defrost	Windshield Cover - Cab
Light Bar 12-48"	Windshield Washer
Outboard Motor	Windshield Wiper
Rear Accessory Carrier - Main Mount	