

2024 Mudd-Ox 8x8 Vengeance

Engine

Type	Gasoline EFI	
Model	VEN31	VEN40
Brand	Kohler	Briggs & Stratton
Power Output	31 HP / 23.1 kW	40 HP / 30 kW
Torque	47.1 lbs. / 63.9 Nm	58.5 lbs. / 79.3 Nm
Displacement	50.3 CI / 824 CC	60.6 CI / 993 CC
Cooling	Liquid-Cooled	Air-Cooled
Electrical	25 Amp, 60 Opt	50 Amp, 105 Opt
Battery	34 Series	

Transmission

Transmission	Skid Steer T20 Dual Planetary with Split Shift for counter-rotation capability.
Brakes	Transmission/Mechanical
Clutch	CVT Continuously Variable Clutch maximizes engine power to transmission

Controls & Instrumentation

Steering	Left & Right Steering Sticks
Parking Brake	Ratchet Style Mechanical
Instrumentation	Analog Dash Panel Left Mount
Gauges	Fuel Gauge Volt Meter Water Temperature [G] Transmission Fluid Temperature Hour Meter
Warning Lights	Engine Diagnostics (VEN31, VEN40) Low Oil Pressure Parking/Emergency Brake Tachometer (VEN40)
Throttle Cable	Heated Throttle Cable w/Aluminum Base

Chassis, Body & Lights

Frame	Powder coated steel for long life
Drive System	Standard Chain: Transmission single 60, rear four axles single 60. Front four axles twin HD Upgrade: Transmission twin 50, all axles twin 60.
Axles	1,500" Solid steel with locking hubs
Body	Vacuum formed upper body, lower hull and skid plate made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" Mudd-Ox Vendetta on 12" Mudd-Ox Bead Lock Rim
Lights	LED Headlights LED Tail Lights

Performance

Speed - Land	17-25 mph (27-40 km/h) [A]
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	1,800 lbs. (816 Kg) (Distributed evenly) Less the weight of any accessories [C]
Load Capacity - Water	1,000 lbs. (454 Kg) (Distributed evenly) Less the weight of any accessories [C]
Turning Circle	Zero turning Radius
Towing Capacity	2,000 lbs. (907 Kg) [H]
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]
Rear Bench Seat	Optional

Safety

Safety	Standard Fold Down Roll Over Protection System - Rear Roll Over Protection System available as an option. Front Seat Belts.
Fuel Capacity	10.5 US Gallons
Operating Conditions	All Weather, all terrain, -40° F to +110° F (-40° C to +43° C)

Ground Clearance & Ground Pressure

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 2 psi [D] Tracks 0.5 psi [D]

Operation & Convenience

Self-Extraction Winch	5,000 lb. Winch Standard
Storage	Lockable Glove Box Cup Holders 12" x 28" Insert area over engine cover for holding light cargo
Electrical Output	Single 12 Volt Outlet Dual Port USB Outlet
Bilge Pump	Standard

Weight & Dimensions

Shipping Weight	2,000 lbs.
Dimensions	123" long by 68" wide by 79" high with roll bar up. 61" high with roll bar down (on 26 x 14 x 12" Vendetta Tires)
Approach and Departure Angles	25 degrees maximum

Warranty

Warranty	1 year or 500 hours limited warranty on Mudd-Ox Engine: See manufacturer's manual [E]
----------	---

Specifications are subject to change without notice.

[A] Top speed depends on terrain conditions and drive train options.

[B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)

[C] See Owner's manual for accessory listing and weight.

[D] Capacity includes occupants, cargo, and installed accessories.

[E] See Owner's Manual for full warranty information.

[F] Provides better flotation and allows for more carrying capacity in the water.

[G] Only When equipped with 31 HP Kawasaki engine

[H] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

A/C Unit (VEN40 only)	Light Bar 12-48"
A/C Unit Brush Guard	Outboard Motor
Alternator Upgrade	Rear Accessory Carrier - Main Mount
Automatic Chain & Bearing Lubrication	Rear Seat - Standard
Auxiliary Switch Panel	Rear Seat - Bench
Axle Locking Hubs	Rescue
Bearing Extension Kit	Safari Rack (Full/Half Lengths)
Bearing Grease Zerk Relocation	Snow Plow - 85"
Brush Cage (Full/Half Length)	Snow Plow - Boss V Blade
Brush Guard	Spare Carrier - 5 Gallon Fuel Can w/ Can
Cab - Aluminum	Spare Carrier - Tire
Cab - Canvas (Full/Half Combo)	Tire - Dual Wheel Kit
Cab - Canvas Rear Enclosure	Tool Box
Cab - Stereo Kit	Tracks - 16" Wide Adair
Cargo Liner	Tracks - 20" Wide Ripsaw
Cargo Platform	Transport Tie Downs
Chain HD Upgrade	Twin Roll Bar Package
Dump Bed	Winch - 5000 lbs. Rear Mount
Engine Remote Oil Drain	Winch - Synthetic Rope Upgrade
Fender Kit	Windshield
Float - Catwalk	Windshield Cover - Cab
Float - Front	Windshield Washer
Heater w/ Defrost (VEN31)	Windshield Wiper

Mudd-Ox, Inc.
8525 W 750 N
Shipshewana, IN 46565
Phone: 260-768-7221
Fax: 260-768-3074
www.muddox.net
info@muddox.net

Mudd-Ox

Custom Colors Available Upon Request

